



ROCKDRILL OILS ISO 150/220/320/460

DESCRIPTION

LUBEFUSION ROCKDRILL OILS is a range of premium quality virgin base oils. They contain extreme pressure additives and are suitable for all types of rockdrills. Additives used in the formulation gives good wear protection coupled with excellent corrosion resistance. The oil has excellent adhesion to metal to ensure good boundary lubrication hence longer equipment life.

APPLICATION

LUBEFUSION ROCKDRILL OILS may be used on any type of pneumatic rockdrills. They give good wear protection to the components and provide excellent anti-corrosion properties

PERFORMANCE

No set performance limits

ADVANTAGES

- Good wear protection
- Excellent corrosion protection
- Resistance to water washout

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	100	150	220	320	460	Method
ISO Grade		100	150	220	320	460	
Viscosity @ 40°C	cSt	100	150	220	320	460	ISO 3104
Flash Point (Min)	°C	230	240	240	250	265	ISO2592

WARRANTY - All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

1/...