



GEAR OIL EP 85W140 GL 5

DESCRIPTION

Gear Oil EP85W140 GL5 is a high performance, multipurpose EP gear lubricant for differentials, manual transmissions other gear cases of automotive equipment.

APPLICATION

Gear Oil EP 85W140 GL5 is recommended for gear applications requiring lubricants which meet MIL-L-2105D, MIL-L-2105B, API Service GL-5, where EP multipurpose of hypoid type gear oils are specified. It is particularly suitable where loading is severe and maximum gear protection is required. This product may also be used for top up of limited slip differentials after break in of new or rebuilt units.

PERFORMANCE

Meets or exceeds:

- API SERVICE CATEGORIES GL5
- MIL-L-2105D AND MIL-L-2105B (85W)- FORMER US MILITARY SPEC
- MACK GO-H AND GO-G
- MAN 342 N

ADVANTAGES

- High performance, EP additive system controls transmission gear tooth wear, excellent load carrying capacity to protect gear equipment against surface stress under heavily loaded conditions
- GL-5 gear oils have been fortified with anti-wear, anti-oxidant, anti-foam, anti-corrosion and extreme pressure additives

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	EP 85W140 GL 5	Method
Density @ 20°C	Kg/L	0.91	ASTM D-1298
Flash Point (COC)	°C	238	ASTM D97
Viscosity 40°C	cSt	350	ASTM D-445
Viscosity 100°C	cSt	25	ASTM D-445
Viscosity Index	VI	95	ASTM D2270
Pour Point	°C	-18	ASTM D93

WARRANTY - All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.