



GEAR OILS EP 90 AND EP 80W90 GL 4

DESCRIPTION

High performance, multipurpose mild to extreme pressure gear lubricant.

APPLICATION

Manual transmissions, transaxles, planetary hub and other spur gear axles which specifically require mild EP gear oils meeting API GL4.

PERFORMANCE

Meets or exceeds:

- API GL 4
- MULTIPURPOSE EP OR HYPOID GEAR OIL
- MIL-2105
- MB 235.1 – MB 235.5
- MAN 34ML

ADVANTAGES

- High performance, EP additive system controls transmission gear tooth wear, excellent load carrying capacity to protect gear equipment against surface stress under heavily loaded conditions
- GL-4 gear oils have been fortified with anti-wear, anti-oxidant, anti-foam, anti-corrosion and extreme pressure additives.

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	EP90	80W90	Method
Density @ 20°C	KG/L	0.875	0.875	ASTM D-1298
Viscosity 40°C	cSt	170	190	ASTM D-445
Viscosity 100°C	cSt	15	15	ASTM D-445
Viscosity Index (Min)	VI	95	95	ASTM D2270
Pour Point (Max)	°C	-22	-15	ASTM D93
Flash Point (Min)	°C	220	222	ASTM D97
Sulphur, WT	%	0.4	0.4	ASTM D-4951

WARRANTY - All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.