



## Lubefusion Brake Fluid DOT 3 D.O.T. 3 Hydraulic Brake Fluid

### Description / Application

Lubefusion Brake Fluid DOT 3 is a hydraulic brake fluid typically used for aftermarket applications. Lubefusion Brake Fluid DOT 3 is designed for use where a DOT 3 Motor Vehicle Brake Fluid is recommended by the motor vehicle manufacturer.

### Specifications

Lubefusion Brake Fluid DOT 3 meets and exceeds the requirements of the following specifications for a DOT 3 brake fluid:

- FMVSS / CMVSS 116
- SAE J1703
- ISO 4925

### Packaging

Lubefusion Brake Fluid DOT 3 is available in 20L, 5L, 500ml, 200ml containers.

### Storage

Lubefusion Brake Fluid DOT 3 should be stored in its original container until use. Brake fluids are hygroscopic by nature. Containers should be kept sealed to prevent the absorption of moisture.

### Safety Precautions

Refer to Material Safety Data Sheet.

### Shelf Life

Lubefusion Brake Fluid DOT 3 has a recommended shelf life of 2 years from the manufacture date.

### Typical Properties

#### Equilibrium Reflux Boiling Point

Dry	258°C
Wet	151°C

Viscosity	-40°C	1108 cSt
	100°C	2.0 cSt

pH	9.4
----	-----

Color	Amber
-------	-------

Density	1.044 g / cm <sup>3</sup>
---------	---------------------------

