



Lubefusion D.O.T. 4 Hydraulic Brake Fluid

Description / Application

Lubefusion Brake Fluid DOT 4 is a hydraulic brake fluid typically used for aftermarket applications. Lubefusion Brake Fluid DOT 4 is designed for use where a DOT 4 Motor Vehicle Brake Fluid is recommended by the motor vehicle manufacturer.

Specifications

Lubefusion Brake Fluid DOT 4 meets and exceeds the requirements of the following specifications for a DOT 4 brake fluid:

- FMVSS / CMVSS 116
- SAE J1704
- ISO 4925

Packaging

Lubefusion Brake Fluid DOT 4 is available in 20L, 5L, 500ml, 200ml containers.

Storage

Lubefusion Brake Fluid DOT 4 should be stored in its original container until use. Brake fluids are hygroscopic by nature. Containers should be kept sealed to prevent the absorption of moisture.

Safety Precautions

Refer to Material Safety Data Sheet.

Shelf Life

Lubefusion Brake Fluid DOT 4 has a recommended shelf life of two years from the manufacture date.

Typical Properties

Equilibrium Reflux Boiling Point

Dry 263°C

Wet 161°C

Viscosity -40°C 1450 cSt
100°C 2.1 cSt

pH 8.0

Color Amber

Density 1.062 g / cm³

