



CUTTER BAR/ CHAIN SAW OIL LFC150

DESCRIPTION

LubeFusion Cutter Bar Lube 150 is a specially formulated chain saw lubricating oil designed to meet the special requirements of a chain saw operating in the extreme conditions of the South African climate.

APPLICATION

- Chain saw lubrication.
- Cutter bar lubrication.

PERFORMANCE

Meets or exceeds:

- No specification standard has been set for this product.

ADVANTAGES

- LubeFusionCutter Bar Lube 150 grips tightly to the chain because of its tacky nature. This ensures that it does not get flung off from the chain and cutter bar during operation.
- The medium viscosity oil ensures excellent chain penetration and the anti-wear and lubricity additives provide excellent lubrication and minimize wear of the cutter bar and chain.
- The low pour point ensures that the oil will perform even in the middle of the coldest winter.

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Heading Here	Method
Viscosity @ 40°C	cSt	150	ASTM D 445
Viscosity @ 100°C	cSt	16	ASTM D 445
Viscosity Index Min		110	ASTM D2270
Density @ 20°C	Kg/L	0.885	ASTM D4052
Flash Point Min	°C	170°C	ASTM D97
Pour Point Max	°C	-17°C	ASTM D93

WARRANTY - All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.