



COMPRESSOR OILS 32, 46, 68 & 100

DESCRIPTION

Compressor Oils is a range of premium quality highly refined virgin paraffinic base oils. They contain a balanced additive system consisting of anti-wear, anti-rust, anti-oxidant and anti-foam additives to give outstanding levels of performance for use in reciprocating air, vane, rotary and piston compressors.

APPLICATION

- Reciprocating air, vane, rotary and piston compressors

PERFORMANCE

Meets or exceeds:

- DENISON HFO, HF-1, HF-2
- VICKERS EATON I-286-5 INDUSTRIAL EQUIPMENT
- VICKERS EATON M-2950-85 MOBILE EQUIPMENT
- CINCINATI MACHINE P68, P69, P70
- BOSCH REXROTH RE 90, 220
- DIN 51524 PART I, II AND III
- ISO 11158 CATEGORIES HH, HL, HM AND HV
- ASTM D6158-99
- DIN51524, Part 2 & 3 (HLP, HVLP) Afnor NF E 48-603
- DIN51517 part 2 TLV 9013
- Cincinnati P38, P55, P54, P57 and P62 DIN51515 part 1 & 2
- BS489 GE GEK 32568 A/C
- CEGB 207001 MIL -L-17672 D
- BB HTGD 90117 US Steel 120
- DP 6521 (DAA,DAB,DAH,DAG)
- DIN 51506 (VBL, VCL, VDL)
- VDMA 24568

ADVANTAGES

- Outstanding overall performance
- Extended service intervals
- Excellent oxidation resistance
- Excellent corrosion inhibitors
- Excellent separation from water (IP19 and D1401)
- Excellent rust control even after water wash
- Resistance to sludge formation / filterability
- Ashless/ calcium free

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	32	46	68	100	Method
Viscosity @ 40°C	cSt	32	46	68	100	ASTM D 445
Viscosity @ 100°C	cSt	5	7	8	9.8	ASTM D 445
Flash Point	°C	207	210	215	220	ASTM D97

2/...

- 2 -

WARRANTY - All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.