



## Company Details

<u>Name</u>	PACE OIL	<u>Emergency Tel</u>	0800202202
<u>Address</u>	4 Spindle Street Boltonia, Krugersdorp Gauteng R.S.A	<u>Tel</u>	+2711665-3754
		<u>Fax</u>	+2711665-4626

## 1. Product and Company Identification

<u>Trade / Commercial Name</u>	<b>GREASE MULTI PURPOSE EP 2MT</b>		
<u>Chemical Name</u>	environmentally hazardous substance, solid, NOS		
<u>Formula</u>			
<u>Chemical Family</u>			
<u>Synonyms</u>			
<u>Un No</u>	3077	<u>Hazchem Code</u>	2z
<u>ERG No</u>	171	<u>EAC</u>	31

## 2. Hazards Identification

Miscellaneous - Substances - Low to Moderate Hazard

Some may burn but none ignite readily. Some may polymerize (P) explosively when heated or involved in a fire.

Containers may explode when heated.

Inhalation of material may be harmful. Contact may cause burns to skin and eyes.

Fire may produce irritating, corrosive and/or toxic gases. Runoff from fire control may cause pollution.

## 3. Composition

<u>Hazardous Components</u>	Blend of refined mineral oils and additives. Lithium complex grease with a high viscosity oil. (ISO VG 460)
-----------------------------	--

## 4. First Aid Measures

<u>First Aid Skin</u>	Remove & isolate contaminated clothing, including shoes. Flush skin with running water for 20 minutes.
<u>First Aid Eyes</u>	Flush eyes with water for 20 minutes.

<u>First Aid Ingested</u>	Hold eyelids open while washing. Do not induce vomiting. Wash out mouth with water. Seek medical treatment.
<u>First Aid Inhalation</u>	Move victim to fresh air. If not breathing give artificial respiration. If breathing of victim is difficult administer oxygen for a maximum period of one hour.

## **5. Fire Fighting Measures**

Small Fires: Dry chemical, CO<sub>2</sub>, water spray or regular foam.

Large Fires: Water spray, fog or regular foam.

Move containers from fire area if you can do it without risk.

Do not scatter spilled material with high pressure water streams.

Dike fire-control water for later disposal.

Fire involving Tanks: Cool containers with flooding quantities of water until well after fire is out.

Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.

ALWAYS stay away from the ends of tanks.

Isolate spill or leak area immediately for at least 10 to 25 metres (30 to 80 feet) in all directions.

Keep unauthorized personnel away. Stay upwind.

Wear positive pressure self-contained breathing apparatus (SCBA).

Structural firefighters' protective clothing will only provide limited protection.

If ROAD OR RAIL TANKER is involved in a fire, ISOLATE for 800 metres (1/2 mile) in all directions;

also, consider initial evacuation for 800 metres (1/2 mile) in all directions.

## **6. Accidental Release Measures**

### **PRECAUTIONS:**

Restrict access to area.

Provide adequate protective equipment and ventilation.

Remove sources of heat and flame.

Notify occupational and environmental authorities.

### **SPILL OR LEAK:**

Do not touch or walk through spilled material.

Stop leak if you can do it without risk.

#### **Small Dry Spills**

With clean shovel place material into clean, dry container and cover loosely; move containers from spill area.

#### **Large Spills**

Cover powder spill with plastic sheet or tarp to minimize spreading.

Prevent entry into waterways, sewers, basements or confined areas.

## **7. Handling And Storage**

When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Prevent spillages.

Storage: Keep in a cool, dry, well-ventilated place. Use properly labelled and closable containers.

Avoid direct sunlight, heat sources, and strong oxidizing agents.

Storage temperature: 0°C minimum to 50°C maximum.

Recommended materials: For containers or container linings, use: mild steel or high density polyethylene.

Unsuitable materials: For containers or container linings, avoid: PVC.

Other information: Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

## **8. Exposure Controls/Personal Protection**

Occupational Exposure Limits Threshold limit values are given below.

Lower exposure limits may apply locally:

Component name	Limit type	Value	Unit	Other information
----------------	------------	-------	------	-------------------

Oil mist, mineral	8-hour TWA	5	mg/m <sup>3</sup>	ACGIH
-------------------	------------	---	-------------------	-------

	15-min STEL	10	mg/m <sup>3</sup>	ACGIH
--	-------------	----	-------------------	-------

Controls

The control measures appropriate for a particular worksite depend

on how this material is used and on the extent of exposure.

The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release.

Use a non-sparking, grounded ventilation system separate from other

exhaust ventilation systems. Exhaust directly to the outside.

Supply sufficient replacement air to make up for air removed.

Have a safety shower/eye wash fountain readily available in the immediate work area

Personal Protection

If engineering controls and work practices are not effective in controlling this material, then wear suitable personal protection

equipment, including chemical safety goggles & face shield, boots,

imperious gloves, coveralls, & respiratory protection.

Have appropriate equipment available for use in emergencies.

## **9. Physical & Chemical Properties**

NLGI Grade 2 MT

Colour Moly Grey

Texture Smooth and Tacky

Work Penetration 265 - 295

Dropping Point °C 260 (500°F)

Water Washout (Max) % 10.0

Water Spray Off (Max) % 25  
Rust Prevention Pass  
Copper Corrosion 1b  
Oxidation Stability Psi 10  
Oil Separation 4 Ball Wear  
Scar Dia(Max) 0.60  
4 Ball EP Weld Point kg 315  
Load Wear Index kgf 45  
Timken OK Load kg 27.2 (60lbs)

Base Oil Characteristics:  
Base Oil Viscosity D-445 @40°C cSt 410-510  
Base Oil Viscosity D-445 @100°C cSt 20-30  
Working Temperature (up to) °C 182

## **10. Stability And Reactivity**

<u>Conditions to Avoid</u>	Stable. Avoid extremes of temperature and direct sunlight.
<u>Incompatible Materials</u>	Strong oxidizing agents.
<u>Other</u>	Hazardous decomposition products are not expected to form during normal storage.

## **11. Toxicological Information**

Toxicological data has not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products.

Acute toxicity - oral: LD50 expected to be above 2000 mg/kg.  
Acute toxicity - dermal: LD50 expected to be above 2000 mg/kg.  
Acute toxicity - inhalation: Not considered to be an inhalation hazard under normal conditions of use.

Eye irritation: Expected to be slightly irritant.  
Skin irritation: Expected to be slightly irritant.  
Respiratory irritation: If mists are inhaled, slight irritation of the respiratory tract could occur.  
Skin sensitization: Normally not expected to be a skin sensitizer  
Carcinogenicity: Information is based on mineral oils of types shown to be non-carcinogenic in animal skin-painting studies.  
Mutagenicity: Not considered to be a mutagenic hazard.  
Other information: Prolonged and/or repeated contact with this product can result in defatting of the skin, particularly at elevated temperatures.  
This can lead to irritation and possibly dermatitis, especially under conditions of poor personal hygiene.  
Skin contact should be minimised.  
Used engine oils may contain harmful impurities that have accumulated during use.  
The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.  
ALL used oil should be handled with caution and skin contact avoided as far as possible.

## 12. Ecological Information

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of normal components and the ecotoxicology of similar products.

Mobility: Liquid under most environmental conditions. Floats on water.

If it enters soil, it will adsorb to soil particles and will not be mobile.

Persistence/degradability: Not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

Bioaccumulation: Has the potential to bioaccumulate.

Ecotoxicity: Poorly soluble mixture. Product is not chronically toxic at 1 mg/L.

May cause physical fouling of aquatic organisms.

## 13. Disposal Considerations

<u>Disposal Method Product</u>	There are no uniform EC regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding laws and regulations. We recommend that you contact the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste.
<u>Disposal Method Packaging</u>	Disposal in accordance with local legal provisions.

## 14. Transport Information

<u>UN No</u>	3077 <u>Hazchem Code</u>	2z
<u>ERG No</u>	171 <u>EAC</u>	31
<u>IMDG-Shipping Name</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	
	<u>IMDG-Packaging Group</u>	III
<u>Marine Pollutant</u>	Yes	
<u>Class</u>	Class: 9 Miscellaneous Group: III	
<u>Subsidiary Risks</u>	None.	

## 15. Regulatory Information

<u>EEC Hazard Classification</u>	9
<u>Risk Phases</u>	Danger of cumulative effects
<u>Safety Phases</u>	This material and its container must be disposed of in a safe way

**16. Other Information**

Reason for Alteration: General update.

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properness of the product.

**Disclaimer:**

\*\*\*\*\*

The company provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. THE COMPANY MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, THE COMPANY WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION. \*\*\*\*\*

LAST PAGE

All information is given in good faith but without guarantee in respect of accuracy & no responsibility is accepted for errors or omissions or the consequences thereof.