



HYDRAULIC OILS 32, 46, 68, 100, 150, 220MVI

DESCRIPTION

Lubefusion MVI hydraulic fluids are shear stable, **multi-grade** high viscosity index hydraulic fluids designed for use in hydraulic systems with high operating temperatures.

APPLICATION

- Industrial hydraulic systems
- hydraulic couplings
- Industrial torque converters
- Compressors
- Hydraulic on construction and mobile equipment
- Industrial circulating systems
- Hydraulic systems that have gear, vane or piston pumps
- Machine tools
- Plastic injection moulding equipment

PERFORMANCE

Meets or exceeds:

- DIN 51524 PART 2, (JSO 32, 46, 68,150,220)
- ISO STANDARD 6743 PART 4, TYPE HR
- AAMA STANDARD 524 PART 2 (ISO 32, 46, 68,150,220)
- US STEEL 126 AND 127
- VICKERS M-2952-S, 1-286-S (INDUSTRIAL APPLICATIONS), M-2950-S (MOBILE APPLICATION)
ISO 32, 46, 68,150,220
- DENISON HYDRAULICS HF-O (ISO 32, 46, 68,150,220)
- ASTM D 6158 TYPE HM
- GM LS2
- EATON BROCHURE 694 FOR 35VQ25

ADVANTAGES

- Formulated to minimise corrosion, oxidation, foaming and machinery wear for use in highly stressed gear, vane and piston type hydraulic systems where high levels of anti-wear performance are needed.
- They also contain a shear stable Viscosity Modifier which maintains a higher viscosity at elevated temperatures compared to normal hydraulic oils.
- With conventional hydraulic fluids in systems with high working temperatures (>100°C), the fluid viscosity can be reduced to levels which can cause rapid wear or equipment seizure. Lubefusion MVI fluids incorporate polymers to maintain adequate viscosity at high working temperatures.
- As with other Lubefusion hydraulic oils, the MVI range meets the performance specifications of leading manufacturers of hydraulic equipment.

2/...

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	32	46	68	100	150	Method
Colour		Blue	Blue	Blue	Blue	Blue	visual
ISO Grade		32	46	68	100	150	
Viscosity @ 40°C	cSt	32	46	68	100	150	ISO 3104
Air Release@ 50°C	Min's	6.5	9	11	21	29	ISO 9120
Viscosity Index	VI	120	120	120	120	120	ISO2909
Flash Point (Min)	°C	175	180	180	180	200	ISO2592
Pour Point (Max)	°C	-30	-27	-24	-21	-18	ISO3016
FZG Pass Load Stage (Min)		10	10	10	10	10	ISO14635-1
Water separation -time to 3ml emulsion at 54°C max	Min	30	30	30	-	-	ISO 6614
Copper corrosion, 100°C, 3h Max	Class	2	2	2	2	2	ISO 2160

WARRANTY - All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.