



AUTOMATIC TRANSMISSION FLUID [DEXRON II] (ATF DXII)

DESCRIPTION

ATF DXII is an automatic transmission fluid for use where manufacturers call for a Dexron II fluid. It is blended from virgin base oils, which have been fortified with anti-wear anti-oxidant, anti-foam, anti-corrosion and viscosity index improvers together with friction modifiers. This blend of components gives high levels of performance and long service life.

APPLICATION

- Automotive heavy-duty automatic transmissions
- Power shift transmissions
- Power steering
- Certain manual transmissions

PERFORMANCE

Meets or exceeds:

- DEXRON II
- DAIMLER BENZ 236.1 and 236.5
- DENISON HF-0
- ZF TE – ML02F/03D/04D/14A/14C
- VOITH G607
- ALLISON C-4

ADVANTAGES

- Excellent anti-wear properties ensure longer equipment life.

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	ATF DXII	Method
Density @ 20°C	Kg/L	0.86	ASTM D-1298
Viscosity 40°C	cSt	45	ASTM D-445
Viscosity 100°C	cSt	6 - 7.2	ASTM D-445
Viscosity Index	VI	140	ASTM D2270
Pour Point (Max)	°C	-42	ASTM D93
Flash Point (Min)	°C	193	ASTM D97

WARRANTY - All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.