



AUTOMATIC TRANSMISSION FLUID [DEXRON III] (ATF DXIII)

DESCRIPTION

ATF DXIII is an automatic transmission fluid for use where manufacturers call for a Dexron III fluid. It is blended from **very highly refined virgin base oils**, which have been fortified with anti-wear anti-oxidant, anti-foam, anti-corrosion together with friction modifiers. This blend of components gives high levels of performance and long service life.

APPLICATION

- Automotive heavy-duty automatic transmissions
- Hydraulic systems
- Power shift transmissions
- Screw type air compressors
- Power steering
- Certain manual transmissions

PERFORMANCE

Meets or exceeds:

- DEXRON IIIH/IIIG
- FORD MERCON
- ALLISON C-4
- M2C 138CJ/ 166H
- DAIMLER BENZ 236.1
- DENISON HF-0
- CAT TO-2
- VOITH
- POWER STEERING

ADVANTAGES

- Excellent anti-wear properties ensure longer equipment life.

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	ATF DXIII	Method
Density @ 20°C	Kg/L	0.857	ASTM D-1298
Viscosity 40°C	cSt	33	ASTM D-445
Viscosity 100°C	cSt	7.2	ASTM D-445
Viscosity Index	VI	189	ASTM D2270
Pour Point (Max)	°C	-47	ASTM D93
Flash Point (Min)	°C	210	ASTM D97

WARRANTY - All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your

consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.